PRO X DRIP OIL

WELL PUMP DRIP OIL



PRODUCT DESCRIPTION

Pure Drip Oil For Deep-Well Turbine Pump Lubrication

PRO X Drip Oil is an extremely clean low viscosity oil designed to lubricate the shaft bearings of down-hole turbine pumps in agricultural use.

PRODUCT APPLICATION



- Vertical turbine bearing lubrication for deep-well water pumps
- · Anywhere clean, light low-viscosity lubrication is needed

FEATURES AND BENEFITS



- Low Viscosity: Select base stocks are within the viscosity range for pump bearing lubrication as well as a wide variety of other functional uses. Flows in all weather conditions.
- High Stability: Superior refining techniques result in outstanding oxidation, thermal, and color stability, and no sulfur or polar compounds.
- **Colorless**: Severely hydro-treated base stocks are easy to see through and not likely to stain.
- Biodegradable: Unadulterated highly-saturated base stocks are inherently biodegradable.
- Non-Additized: High purity and extremely low odor allow multiple applications for this oil.

TYPICAL TEST DATA

GRAVITY, SPECIFIC	0.862
GRAVITY, "API	32.6
DENSITY, LB./GAL.	7.2
COLOR	PALE
COLOR, ASTM	O.5 MAX
ODOR	CHARACTERISTIC
TAN	0.01
FLASH POINT, °C TYP	190
VISCOSITY AT 40°C, CST	14
VISCOSITY AT 100°F, SUS	77

SPECIFICATIONS

Recommended for use in all deep-well turbine systems, including those from:

- Goulds
- Berkeley
- · American/National Pump
- Franklin Electric
- Sargent



