PRO X FORM OIL

Release Agent for Concrete Forms



PRODUCT DESCRIPTION

Non-additized Oil For Preventing Concrete From Adhering To Forms

PRO X Form Oil is a straightforward oil-based environmentally friendly concrete release agent designed to be applied to concrete forms.

PRODUCT APPLICATION



- Wood forms used in concrete construction
- · Metal forms used in concrete construction
- · Concrete Tool surfaces
- Other surfaces where a light, oily barrier is desired

FEATURES AND BENEFITS



- Excellent Release Characteristics: Light oil provides a barrier between cement and form surfaces, with no build-up.
- Safe To Use: Highly refined, non-additized oil is considered non-hazardous.
- Reduces Rust and Corrosion: Slows or stops rust of metal form and tool surfaces.
- Environmentally Friendly: All components are inherently biodegradable.
- Easily Applied: Ready-to-use product needs no dilution, and can be applied by swabbing, brushing, or spraying.
- Other Uses: Anywhere a light, non-additive oil is desired.

TYPICAL TEST DATA

GRAVITY, SPECIFIC	0.862
GRAVITY, °API	32.6
DENSITY, LB./GAL.	7.2
COLOR	PALE
COLOR, ASTM	O.5 MAX
ODOR	CHARACTERISTIC
FLASH POINT, °C TYP	190
VISCOSITY AT 40°C, CST	14
VISCOSITY AT 100°F, SUS	77



