

PRO X LOG AND SHAKE OIL

Wood Treatment Oil



PRODUCT DESCRIPTION

Light Mineral Oil For Treating Certain Exterior Wood Surfaces

PRO X Log and Shake Oil is an environmentally friendly low viscosity treatment that revitalizes and improves the weather resistance of exterior wood products.

PRODUCT APPLICATION

- Wood shake shingles that require mineral oil treatment
- Exterior cabin logs which need regular oil treatment
- Untreated landscaping timbers
- Certain other exterior wood products

FEATURES AND BENEFITS

- **Exterior Wood Protection:** Light oil readily penetrates wood surfaces and provides a barrier to weather elements.
- **Safe To Use:** Highly refined, non-additized oil is considered non-hazardous.
- **Environmentally Friendly:** All components are inherently biodegradable.
- **Easily Applied:** Ready-to-use product needs no dilution, and can be applied by swabbing, brushing, or spraying.
- **Other Uses:** Anywhere a light, non-additive oil is desired.

TYPICAL TEST DATA

GRAVITY, SPECIFIC	0.862
GRAVITY, °API	32.6
DENSITY, LB./GAL.	7.2
COLOR	PALE
COLOR, ASTM	0.5 MAX
ODOR	CHARACTERISTIC
FLASH POINT, °C TYP	190
VISCOSITY AT 40°, CST	14
VISCOSITY AT 100°F, SUS	77



Call Now (800) 964-0076 | Learn More GoPROX.com

PCMO | HDMO | Coolants | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE