

PRO X MULTIVEHICLE ATF

Multivehicle Automatic Transmission Fluid



PRODUCT DESCRIPTION

Modern Automatic Transmission Fluid for Use in Many Automotive and Light Truck Transmissions

PRO X Multivehicle ATF is a synthetic blend formulation created to work in a broad range of domestic and foreign automatic transmissions.

PRODUCT APPLICATION

- Ford vehicles calling for Mercon® V or Mercon® in the transmission
- GM vehicles from 2005 and earlier, except for CVTs
- Chrysler vehicles, except for CVTs and DCTs
- Certain imported cars and trucks that called for a high-vis ATF
- Powershift and HD automatic transmissions in trucks and buses that call for ATF of this type
- Mobile hydraulic systems that call for an ATF as the hydraulic fluid
- Not suitable for use in transmissions requiring low-vis ATF or CVT fluid

FEATURES AND BENEFITS

- **Wear Prevention:** Ashless antiwear and shear-stable viscometric additives provide excellent protection of metal transmission surfaces including planetary gears, pumps, internal bearings, and bands.
- **Oil Life:** Outstanding antioxidant properties greatly extend the oil service life in spite of demanding transmission operating conditions.
- **Frictional Properties:** Premium friction modifier and antishudder additives provide the smooth shifting expected from the transmission and maintain that performance over time.
- **Low Temperature Performance:** The excellent cold weather fluidity is due to synthetic blend stocks and flow additives, leading to better shifting at extremely low temperatures and no cold stalling.
- **Transmission Cleanliness:** Additives prevent deposit and varnish formation on delicate control valves, preventing compromises in shifting.
- **Compatibility:** Formulated to be compatible with all other transmission fluids of this type.

TYPICAL TEST DATA

| | |
|-------------------------|-----------|
| GRAVITY, API | 33.6 |
| VISCOSITY AT 40°C, CST | 34 |
| VISCOSITY AT 100°C, CST | 7.6 |
| VISCOSITY INDEX | >200 |
| FLASH POINT, °C (°F) | 195 (384) |
| POUR POINT, °C (°F) | -45 (-49) |
| COLOR | RED |

SPECIFICATIONS

Recommended for use where the following are cited:

- Dexron® III, IIIG
- Dexron® II, IIE
- Type A Suffix A
- Mercon®
- Mercon® V
- Ford M2C138-CJ
- Ford M2C166-H
- ATF+4
- Allison C-4
- Voith DIWA
- ZF Ecomat



Call Now (800) 964-0076 | Learn More GoPROX.com

PCMO | HDMO | Coolants | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE