PRO X HD 50/50 A/F GREEN

Conventional Heavy Duty Antifreeze/Coolant



PRODUCT DESCRIPTION

Heavy Duty Conventional Coolant Developed for Use In Many Cooling Systems

PRO X HD 50/50 A/F Green has been formulated to offer excellent protection from freezing, overheating, corrosion, and liner pitting for cooling systems in both gasoline and diesel engines.

PRODUCT APPLICATION

- Heavy Duty over-the-road trucks in long-haul or short-haul service
- Medium Duty delivery and other trucks in stop-and-go service
- Heavy Duty off-road, mining, and agricultural equipment
- Passenger cars and light trucks with either gasoline or diesel engines
- Continuous-Duty and Standby generator sets

FEATURES AND BENEFITS

- Freeze Protection: Quality ethylene glycol delivers freeze protection for the entire cooling system, all the way down to extremely low subzero temperatures.
- Reduced Boilover: Boiling point elevation offers an additional buffer of higher temperature operation when the cooling system is being challenged.
- Corrosion Protection: Optimum silicate content provides very good corrosion protection for all wetted surfaces. Premixed with the ideal water chemistry to prevent scale.
- **Pitting Prevention:** Precharged with Supplementary Coolant Additives (SCAs). Ample nitrite levels halt the implosion mechanism that causes diesel liner pitting.

TYPICAL TEST DATA

SPECIFIC GRAVITY RANGE	1.072 - 1.225
GLYCOL CONTENT, WT %	48
PROTECTION RANGE, °F	-34 - 226
COLOR	GREEN
NITRITES, PPM	1200-1400
PH RANGE	9.0 - 11.0
ASH CONTENT, WT % MAX	0.5

SPECIFICATIONS

Recommended for use where the following are cited:

- TMC RP 329
- SAE 1941
- Cummins CES14603
- Case Corp. MS1710
- PRO X HD 50/50 A/F GREEN
- GM 1825
- ASTM D-4985
- GM 1899
- Caterpillar DEAC
- Ford New Holland 9-86
- Freightliner 48-22880
- EMD M.I. 1748E
- Detroit Diesel 7SE298
- Waukesha 4-1974D
- ASTM D-3306
- CID A-A 52624A
- John Deere 8650-5

Suitable for use in most equipment from:

- PACCAR
- MACK
- Navistar
- Thermo-King





