

# PRO X SYN BLEND

AUTOMOTIVE ENGINE OIL



## PRODUCT DESCRIPTION

**Premium Quality Synthetic Blend Motor Oil Specifically Developed for All-Season Use in Modern and Legacy Gasoline Engines**

PRO X Syn Blend is formulated using the most advanced additive technology available to meet the latest fuel economy standards while exceeding the specifications for LSPI prevention, wear control, piston deposits, cleanliness, varnish and sludge, oxidation control, and emission system and seal compatibility. PRO X Syn Blend SAE 5W-20, 5W-30 & 10W-30 Motor Oils each carry the ILSAC GF-6 Certification Mark and meet the API Resource Conserving requirements.

## PRODUCT APPLICATION

- Gasoline engines in cars and light trucks in both individual and fleet service. Meets or exceeds warranty requirements
- Direct injected, high revving and turbocharged passenger car engines
- All engines where API Performance Category SP, SN Plus, SN, SM, SL, or earlier are recommended
- All engines that require oils showing the ILSAC GF-6A Certification Mark (SAE 5W20, 5W30 and 10W30)
- Certain powerboats, motorcycles, and stationary equipment

## FEATURES AND BENEFITS

- **Wear Prevention:** Exceptional Zinc additive package prevents metal-to-metal wear in the valve train and all other critical lubrication conditions.
- **Oil Life:** Semi-synthetic base stocks and multiple antioxidant additives assure durable performance and keep the oil performing its best in between oil changes.
- **Shear Stable:** Superior VI Improver additives resist shear, keeping the oil within viscosity grade, unlike cheap, lower-quality oils.
- **Low Volatility:** Careful selection of the synthetic base stocks reduces oil volatility and eliminates Low Speed Preignition (LSPI) in modern engines.
- **Clean Engine:** Quality detergents and dispersants keep the internal engine components clean, preventing the buildup of sludge and deposits.
- **Improved Economy:** API Resource Conserving designation gives you every bit of mileage that can be realized.

## TYPICAL TEST DATA

SAE GRADE	5W-20	5W-30	10W-30
API SERVICE	SP/EC	SP/EC	SP/EC
ENERGY CONSERVING	YES	YES	YES
ILSAC	GF-6A	GF-6A	GF-6A
API GRAVITY	32.5	32.8	31.9
FLASH POINT, °C (°F)	234 (453)	230 (446)	229 (444)
VISCOSITY AT 40°C, CST	48.4	62.3	65.1
VISCOSITY AT 100°C, CST	8.2	10.4	10.4
VISCOSITY INDEX	144	157	148
COLD CRANK VIS, CP AT °C	6300 (-35)	6300 (-30)	4900 (-25)
PHOSPHORUS, WT%	0.067	0.067	0.077
ZINC, WT%	0.075	0.075	0.085
SULFATED ASH, WT %	0.8	0.8	0.8

## SPECIFICATIONS

**Recommended for use where the following are cited:**

- FCA US (Chrysler) MS-6395
- Ford WSS-M2C945-A, WSS-M2C946-A
- General Motors GM 6094M
- FIAT 9.55535-CR-1

**Registered License:**

API SP, SN Plus, SN, SM, SL, SJ

API "Resource Conserving"

All Previous API "S" Categories

ILSAC GF-6A



Call Now (800) 964-0076 | Learn More [GoPROX.com](http://GoPROX.com)

PCMO | HDMO | Coolants | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE