

PRO X MULTIVEHICLE ATF LV

Lower Viscosity Multivehicle Automatic Transmission Fluid



PRODUCT DESCRIPTION

Fuel Efficient Automatic Transmission Fluid for Use in A Wide Range of the Latest Transmissions

PRO X Multivehicle ATF LV is a full synthetic formulation created to work in a broad range of domestic and foreign automatic transmissions.

PRODUCT APPLICATION

- Ford vehicles calling for Mercon® LV in the transmission.
- GM vehicles calling for Dexron® VI in the transmission.
- Most Chrysler vehicles, except for CVTs and DCTs.
- Most imported cars and trucks that called for a low-vis ATF.
- Mobile hydraulic systems that call for an ATF as the hydraulic fluid.
- Not suitable for use in transmissions requiring Mercon®, Mercon® SP or a CVT fluid.

FEATURES AND BENEFITS

- **Wear Prevention:** Ashless antiwear and shear-stable viscometric additives provide excellent protection of metal transmission surfaces including planetary gears, pumps, internal bearings, and bands.
- **Fuel Economy:** Lower viscosity level improves fuel mileage under all driving conditions.
- **Oil Life:** Synthetic base stock and outstanding antioxidant properties greatly extend the oil service life in spite of demanding transmission operating conditions.
- **Frictional Properties:** Premium friction modifier and antishudder additives provide the smooth shifting expected from the transmission and maintain that performance over the life of the fluid.
- **Low Temperature Performance:** The excellent cold weather fluidity is due to synthetic stocks and flow additives, leading to better shifting at extremely low temperatures and no cold stalling.
- **Transmission Cleanliness:** Additives prevent deposit and varnish formation on delicate control valves, preventing compromises in shifting.
- **Compatibility:** Formulated to be compatible with all other transmission fluids of this type.

TYPICAL TEST DATA

GRAVITY, API	36.0
VISCOSITY AT 40°C, CST	26.2
VISCOSITY AT 100°C, CST	5.9
VISCOSITY INDEX	152
FLASH POINT, °C (°F)	220 (428)
POUR POINT, °C (°F)	-40 (-40)
COLOR	RED

SPECIFICATIONS

Recommended for use where the following are cited:

- Ford Mercon® LV
- Mitsubishi, Kia, Hyundai
SP-III, SP-IV
- GM Dexron® VI
- Acura/Honda Z1, DW-1
- Toyota Type T-IV or WS
- Mopar ATF+4



Call Now (800) 964-0076 | Learn More GoPROX.com

PCMO | HDMO | Coolants | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE