

PRO X SYN BLEND 10W30 HD

HEAVY DUTY ENGINE OIL



PRODUCT DESCRIPTION

Heavy Duty Synthetic Blend Motor Oil For Both On-road and Off-road Engines

PRO X is an excellent quality heavy duty CK-4 motor oil formulated for all modern diesel engines, and is particularly suitable for vehicles with emissions equipment such as Diesel Particulate Filters and Selective Catalytic Reduction systems.

PRODUCT APPLICATION

- Heavy duty over-the-road trucks, in long haul and short-haul service
- Medium duty delivery and other stop-and-go service trucks
- Heavy duty off-road, mining, and agricultural equipment
- Continuous-duty and standby generator sets
- All 4-stroke diesel and gasoline engines where API CK-4 or SN (or prior class) is called for, and where 10W30 is an appropriate viscosity

FEATURES AND BENEFITS

- **Wear Prevention:** Robust high Zinc additive levels and shear-stable viscometrics protect all engine surfaces, especially those in boundary lubrication conditions.
- **Oil Life:** Semi-synthetic base stocks and multiple antioxidant additives assure durable performance and offer the opportunity to extend drain intervals.
- **Deposit & Sludge Control:** An extensively proven detergent/dispersant additive package keeps contaminants and byproducts in suspension, keeping your engine cleaner.
- **Cold Flow Behavior:** Very low temperature flow and viscosity testing exceeds the industry specifications for 10W30 engine oils.
- **Exhaust Aftertreatment Compatible:** Formulated to meet the chemical requirements established to prevent problems with emission equipment such as DPFs and SCR.
- **Backward Serviceable:** Compatible with all earlier API classifications for 4-stroke diesel and gasoline engines, naturally aspirated or turbocharged, satisfying a mixed-age fleet.

TYPICAL TEST DATA

SAE Viscosity Grade	10W30
Specific Gravity	0.87
Flash Point, °f	445
Pour Point, °f	-48
Viscosity at 100°C, cst	11.9
Viscosity at 40°C, cst	81
Cold crank vis, cp @ °c	6200@-25
Viscosity index	143
Base number, mg koh/g	9.6
Sulfated ash, WT %	1.0
Zinc, WT %	0.1100-0.1300

SPECIFICATIONS

Recommended for use where the following are cited:

- ACEA E9
- Caterpillar ECF-3
- Cummins CES 20086
- Detroit Diesel 93K222
- Mack EDS-4.5
- Ford WSS-M2C171-F1
- Renault RLD-3
- Volvo VDS-4.5

Registered License:

API CK-4, CJ-4, CI-4

Plus, CI-4



Call Now (800) 964-0076 | Learn More [GoPROX.com](https://www.GoPROX.com)

PCMO | HDMO | Coolants | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE