## PRO X HD 50/50 A/F GREEN

Conventional Heavy Duty Antifreeze/Coolant



### PRODUCT DESCRIPTION



PRO X HD 50/50 A/F Green has been formulated to offer excellent protection from freezing, overheating, corrosion, and liner pitting for cooling systems in both gasoline and diesel engines.

## PRODUCT APPLICATION

- Heavy Duty over-the-road trucks in long-haul or short-haul service
- Medium Duty delivery and other trucks in stop-and-go service
- Heavy Duty off-road, mining, and agricultural equipment
- Passenger cars and light trucks with either gasoline or diesel engines
- Continuous-Duty and Standby generator sets

## **FEATURES AND BENEFITS**

- Freeze Protection: Quality virgin ethylene glycol delivers freeze protection for the entire cooling system, all the way down to extremely low subzero temperatures.
- Reduced Boilover: Boiling point elevation offers an additional buffer of higher temperature operation when the cooling system is being challenged.
- Corrosion Protection: Optimum silicate content provides very good corrosion protection for all wetted surfaces. Premixed with the ideal water chemistry to prevent scale.
- Pitting Prevention: Precharged with Supplementary Coolant Additives (SCAs). Ample nitrite levels halt the implosion mechanism that causes diesel liner pitting.

#### TYPICAL TEST DATA

SPECIFIC GRAVITY	1.070
GLYCOL CONTENT, WT %	48
PROTECTION RANGE, °F (W/ 15 PSI CAP)	-34 - 265
COLOR	GREEN
NITRITES, PPM	1250
PH RANGE	9.0 - 11.0
SILICATES	125
PHOSPHATES	0

## > SPECIFICATIONS

# Recommended for use where the following are cited:

- ASTM D-3306, D-6210
- BS 6580:2010
- Caterpillar DEAC
- CID A-A 52624A
- CNH MAT 3620
- Cummins CES 14439, 14603
- DAIMLER DBL 7700
- Detroit Diesel 7SE298
- FORD ESE-M97B18-C

- JCB STD0088
- John Deere H24 A1, A2
- MAN 324 Type N
- Navistar CEMS B<sub>-1</sub>
   Type II, MPAPS B<sub>-1</sub>
- Type II
  Perkins (CAT) SEBU
- 7833-03
  TMC RP 329

## Suitable for use in most equipment from:

- PACCAR
- MACK/Volvo
- Thermo-King



