

PRO X HD UNIVERSAL 50/50 A/F GOLD

Nitrite-Free Extended Life Antifreeze/Coolant



PRODUCT DESCRIPTION

Heavy Duty Nitrite-Free OAT Coolant Developed for Extended Fluid Life

PRO X HD Universal 50/50 A/F Gold has been formulated to offer excellent protection from freezing, overheating, corrosion, and liner pitting for cooling systems in both gasoline and diesel engines.

PRODUCT APPLICATION

- Heavy Duty over-the-road trucks in long-haul or short-haul service
- Medium Duty delivery and other trucks in stop-and-go service
- Heavy Duty off-road, mining, and agricultural equipment
- Passenger cars and light trucks with either gasoline or diesel engines
- Continuous Duty and Standby generator sets

FEATURES AND BENEFITS

- **Extended Life:** Modern Nitrite-free OAT formulation allows coolant service intervals to be extended long beyond those of conventional antifreeze.
- **Freeze Protection:** Quality virgin ethylene glycol delivers freeze protection for the entire cooling system, all the way down to extremely low subzero temperatures.
- **Reduced Boilover:** Boiling point elevation offers an additional buffer of higher temperature operation when the cooling system is being challenged.
- **Corrosion Protection:** Modern Organic Acid Technology provides outstanding corrosion protection for all wetted surfaces. Premixed with the ideal water chemistry to prevent scale.
- **Pitting Prevention:** Effective OAT chemistry halts the implosion mechanism that causes diesel liner pitting.
- **Improved Heat Transfer:** The absence of silicate allows better heat transfer to and from metal surfaces, as compared to conventional antifreeze.
- **Easier Maintenance:** Taking care of the antifreeze is simpler since regular addition of Supplementary Coolant Additives (SCAs) is not necessary.

TYPICAL TEST DATA

SPECIFIC GRAVITY RANGE	1.07
GLYCOL CONTENT, WT %	48
PROTECTION RANGE, °F (W/ 15 PSI CAP)	-34 - 265
COLOR	YELLOW
NITRITES, PPM	0
PH	8.3
SILICATES	0
PHOSPHATES	0

SPECIFICATIONS

Recommended for use where the following are cited:

- ASTM D 3306, D 6210
- BS 6580 (British Standard)
- CES 14439, 14603, 14636, SB3666132-04
- CNH MAT 3624
- Daimler DBL 7700.30
- Detroit Diesel 75E298, 93K217
- Duetz H 0685-7, Class DQCCB-14
- GE Jenbacher 1000-201
- John Deere H24C1, JDS-G135
- Komatsu KES 07892
- MAN 324 Type SNF
- MB B800.40-P-0310-01A, 325.3/326.3
- MTU MTL 5048
- MWMDeutz TR0199-99-1115.2091
- Navistar CEMS B-1 Type IIIA, MPAS B-1 Type IIIA
- TMC RP 329/330

Suitable for use in most equipment from:

- VOLVO
- MACK
- Detroit Diesel
- Thermo-King
- Freightliner



Call Now (800) 964-0076 | Learn More GoPROX.com

PCMO | HDMO | Coolants | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE