

PRO X 10W30 GF-7

HEAVY DUTY ENGINE OIL



PRODUCT DESCRIPTION

Premium Quality Synthetic Blend Motor Oil Specifically Developed for All-Season Use in Modern and Legacy Gasoline Engines

PRO X 10W30 GF-7 is formulated using the most advanced additive technology available to meet the latest fuel economy standards while exceeding the specifications for LSPI prevention, wear control, piston deposits, cleanliness, varnish and sludge, oxidation control, and emission system and seal compatibility. PRO X 10W-30 Motor Oil each carries the ILSAC GF-7 Certification Mark and meet the API Resource Conserving requirements.

PRODUCT APPLICATION

- Gasoline engines in cars and light trucks in both individual and fleet service. Meets or exceeds warranty requirements
- Direct injected, high revving and turbocharged passenger car engines
- All engines where API Performance Category SQ, SP, SN Plus, SN, SM, SL, or earlier are recommended
- All engines that require oils showing the ILSAC GF-7A Certification Mark
- Certain powerboats, motorcycles, and stationary equipment

FEATURES AND BENEFITS

- **Wear Prevention:** Exceptional Zinc additive package prevents metal-to-metal wear in the valve train and all other critical lubrication conditions.
- **Oil Life:** Quality base stocks and multiple antioxidant additives assure durable performance and keep the oil performing its best in between oil changes.
- **Shear Stable:** Superior VI Improver additives resist shear, keeping the oil within viscosity grade, unlike cheap, lower-quality oils.
- **Low Volatility:** Careful selection of the base stocks reduces oil volatility and eliminates Low Speed Preignition (LSPI) in modern engines.
- **Clean Engine:** Quality detergents and dispersants keep the internal engine components clean, preventing the buildup of sludge and deposits.
- **Improved Economy:** API Resource Conserving designation gives you every bit of mileage that can be realized.

TYPICAL TEST DATA

SAE GRADE	10W-30
API SERVICE	SP/EC
ENERGY CONSERVING	YES
ILSAC	GF-7A
API GRAVITY	31.3
FLASH POINT, °C (°F)	229 (444)
VISCOSITY AT 40°C, CST	67
VISCOSITY AT 100°C, CST	10.4
VISCOSITY INDEX	142
COLD CRANK VIS, CP AT °C	6500
PHOSPHORUS, WT%	0.072
ZINC, WT%	0.08
SULFATED ASH, WT %	0.8

SPECIFICATIONS

Recommended for use where the following are cited:

- FCA US (Chrysler) MS-6395
- Ford WSS-M2C945-A, WSS-M2C946-A
- General Motors GM 6094M
- FIAT 9.55535-CR-1

Registered License:

API SQ, SN Plus, SN, SM, SL, SJ

API "Resource Conserving"

All Previous API "S" Categories

ILSAC GF-7A



Call Now (800) 964-0076 | Learn More GoPROX.com

PCMO | HDMO | Coolants | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE