

PRO X DRIVE HD

MULTIFUNCTIONAL TO-4 TRANSMISSION AND HYDRAULIC FLUID



PRODUCT DESCRIPTION

Modern Transmission and Drivetrain oil for use in off-road equipment

PRO X DRIVE HD has been formulated to meet or exceed the needs of off-road equipment that utilize TO-4 fluids for use in the hydraulic, transmission, final drive, and hydrostatic drive systems.

PRODUCT APPLICATION

- Caterpillar off-road equipment calling for a TO-4 fluid
- Other off-road construction equipment that utilizes drivetrain oil
- General purpose antiwear hydraulic oil

FEATURES AND BENEFITS

- **Wear Prevention:** High level of Zinc antiwear additive exceeds Caterpillar minimum requirements and protects hydraulic pumps, gears, and transmission components from metal-to-metal contact.
- **Oil Life:** Effective oxidation inhibitor extends fluid life and prevents system-wide sludge, varnish, and deposits.
- **Limited Demulsibility:** Additives absorb small amounts of free water, preventing damage to gears and hydraulic pumps.
- **Proper Frictional Characteristics:** Specialized additives prevent Powershift transmission slippage.
- **Compatibility:** Formulated to be compatible with all other brands of TO-4 fluid.

TYPICAL TEST DATA

SAE GRADE	10W	30	50	60
API GRAVITY	30	29.5	26.4	25
SPECIFIC GRAVITY @ 60°F	0.876	0.879	0.896	0.901
FLASH POINT, COC @ °C (°F)	213 (415)	233 (451)	242 (468)	266 (511)
VISCOSITY, CST @ 40 °C	43.4	95	225	318
VISCOSITY, CST @ 100 °C	6.7	11	19.1	24.5
VISCOSITY INDEX	108	101	96	98
POUR POINT, °C (°F)	-39 (-38)	-32 (-26)	-27 (-17)	-12 (10)

SPECIFICATIONS

Recommended for use where the following are cited:

- Caterpillar TO-4
- Allison C-4 (SAE 30)
- ZF TE-ML D3E
- Vickers (Eaton) M-2950-S
- Also Recommended For:
- API GL-4
- Caterpillar TO-2 (obsolete)



Call Now (800) 964-0076 | Learn More GoPROX.com

PCMO | HDMO | Coolants | DEF | Hydraulic | Transmission | Specialty Lubes | Gear Oils



PURCHASE